

**COWRA**

<b>RWY</b>	<b>(CN)</b>	<b>TORA</b>	<b>TODA</b>	<b>ASDA</b>	<b>LDA</b>
03	(1)	1166 (3825)	1226 (4022) (2.7%)	1166 (3825)	1166 (3825)
21	(1)	1166 (3825)	1226 (4022) (2.3%)	1166 (3825)	1166 (3825)

RWY 21 - Length of APCH/TKOF surface 2500M.

Slope 0.3% down to SW. RWY WID 18 RWS WID 80

15	(3)	1630 (5348)	1706 (5597) (3.19%)	1630 (5348)	1630 (5348)
33	(3)	1630 (5348)	1720 (5643) (1.58%)	1630 (5348)	1630 (5348)

Fence located parallel to and 3M W of RWS not taken into account in the calculation of TODA and STODA GRAD.

Slope 0.1% down to NW. RWY WID 30 RWS WID 90

**SUPPLEMENTARY TAKEOFF DISTANCES**

RWY03 - 950 (3117) (1.9) 1020 (3346) (2.2) 1188 (3898) (2.5)

RWY21 - 878 (2881) (1.6) 1060 (3478) (1.9) 1194 (3917) (2.2)

RWY15 - 809 (2654) (1.9) 1121 (3678) (2.2) 1349 (4426) (2.5)

This page is intentionally blank.